

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 22-Sep-2009

Revision Date 30-Nov-2024

**Revision Number** 5

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF **THECOMPANY/UNDERTAKING**

1.1. Product identifier

**Product Description:** Benzyltrimethylammonium hydroxide, 40% w/w in methanol A14927 **Synonyms** Triton® B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

#### 1.3. Details of the supplier of the safety data sheet

Compa	any
•••mpe	

Cat No. :

	Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific) Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608
E-mail address	begel.sdsdesk@thermofisher.com
1.4. Emergency telephone number	For information <b>US</b> call: 001-800-227-6701 / <b>Europe</b> call: +32 14 57 52 11 Emergency Number <b>US</b> :001-201-796-7100 / <b>Europe:</b> +32 14 57 52 99 <b>CHEMTREC</b> Tel. No. <b>US</b> :001-800-424-9300 / <b>Europe:</b> 001-703-527-3887
Poison Centre - Emergency information services	Ireland : National Poisons Information Centre (NPIC) - 01 809 2166 (8am-10pm, 7 days a week) Malta : +356 2395 2000 Cyprus : +357 2240 5611

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

**Physical hazards** 

Flammable liquids

Category 2 (H225)

Health hazards

#### Benzyltrimethylammonium hydroxide, 40% w/w in methanol

Acute oral toxicity Acute dermal toxicity Acute Inhalation Toxicity - Vapors Acute Inhalation Toxicity - Dusts and Mists Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Specific target organ toxicity - (single exposure) Category 3 (H301) Category 3 (H311) Category 3 (H331) Category 3 (H331) Category 1 A (H314) Category 1 (H318) Category 1 (H370)

#### Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H370 - Causes damage to organs

#### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

#### 2.3. Other hazards

Toxic to terrestrial vertebrates This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	60	Flam. Liq. 2 (H225)

#### Revision Date 30-Nov-2024

## Benzyltrimethylammonium hydroxide, 40% w/w in methanol

Revision Date 30-Nov-2024

				Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Benzenemethanaminium, N,N,N-trimethyl-, hydroxide	100-85-6	EEC No. 202-895-5	40	Skin Corr. 1A (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Components	Reach Registration Number	
Methanol	01-2119433307-44	
Benzyltrimethylammonium hydroxide	01-2120814378-51	

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.			
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.			
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.			
Inhalation	If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.			
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.			
4.2. Most important symptoms and	effects, both acute and delayed			
Difficulty in breathing. Causes burns by all exposure routes Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation				
4.3. Indication of any immediate me	edical attention and special treatment needed			
Notes to Physician	Treat symptomatically.			
SECTION 5: FIREFIGHTING MEASURES				

#### 5.1. Extinguishing media

#### Benzyltrimethylammonium hydroxide, 40% w/w in methanol

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons No information available.

#### 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release of irritating gases and vapors.

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

#### 6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 C Storage Class (LGK) (Germany)

Class 3

#### 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m <sup>3</sup> TWA	TWA: 260 mg/m <sup>3</sup> 8 hr	TWA: 260 mg/m <sup>3</sup> 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m <sup>3</sup> STEL		STEL: 780 mg/m <sup>3</sup> 15 min
			Skin

#### **Biological limit values**

List source(s):

# Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl alcohol		DNEL = 20mg/kg		DNEL = 20mg/kg
67-56-1 ( 60 )		bw/day		bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl alcohol 67-56-1 ( 60 )	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>	DNEL = 130mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg
67-56-1 ( 60 )		sediment dw			soil dw
Benzenemethanaminium,	PNEC = 21µg/L			PNEC = 3.2mg/L	
N,N,N-trimethyl-,					
hydroxide					
100-85-6 ( 40 )					

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
-----------	--------------	--------------------------	------------------------------	------------	-----

#### Revision Date 30-Nov-2024

#### Benzyltrimethylammonium hydroxide, 40% w/w in methanol

Methyl alcohol	PNEC = 2.08mg/L	PNEC = 7.7mg/kg		
67-56-1 ( 60 )		sediment dw		
Benzenemethanaminium,	PNEC = 2.1µg/L			
N,N,N-trimethyl-,				
hydroxide				
100-85-6 ( 40 )				

#### 8.2. Exposure controls

#### **Engineering Measures**

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

Eye Protection	Consilor	(European standard -	
EVE Protection	GOODES		

Hand Protection	Protective gloves
-----------------	-------------------

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Neoprene	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			
Skin and body pro	tection Long sle	eved clothing		

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> Inorganic gases and vapours filter Type B Grey or Ammonia and organic ammonia derivatives filter Type K Green conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

Physical State	Liquid
Appearance	Light yellow
Odor	Odorless

Benzyltrimethylammonium hydroxide, 40% w/w in methanol

Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	15 °C / 59 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
рН	> 13	20% aq. solution
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/w	vater)	
Component	log Pow	
Methyl alcohol	-0.74	
Benzenemethanaminium,	-3	
N,N,N-trimethyl-, hydroxide		
Vapor Pressure	No data available	
Density / Specific Gravity	0.925	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	
9.2. Other information		

**Explosive Properties** 

Vapors may form explosive mixtures with air

**SECTION 10: STABILITY AND REACTIVITY** 

10.1. Reactivity	None known, based on information available
10.2. Chemical stability	Hygroscopic.
10.3. Possibility of hazardous reacti	ions
Hazardous Polymerization Hazardous Reactions	Hazardous polymerization does not occur. None under normal processing.
10.4. Conditions to avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.
10.5. Incompatible materials	Acids. Strong oxidizing agents.
10.6. Hazardous decomposition pro	<u>ducts</u> Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> ), Thermal

Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating gases and vapors.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;	
Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h

(b) skin corrosion/irritation;	Category 1 A
--------------------------------	--------------

(c) serious eye damage/irritation; Category 1

### (d) respiratory or skin sensitization;

 Respiratory
 No data available

 Skin
 No data available

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 ( 60 )	Guinea Pig Maximisation Test		
	(GPMT)		

(e) germ cell mutagenicity;	No data available			
	Did not show mutagenic effects in animal experiments			
(f) carcinogenicity;	No data available			
	There are no known carcinogenic chemicals in this product			

No data available (g) reproductive toxicity; Test method Test species / Duration Study result Component OECD Test Guideline 416 Rat / Inhalation Methyl alcohol NOAEC = 67-56-1 (60) 2 Generation 1.3 mg/l (air) California Proposition 65. Reproductive toxicity. **Reproductive Effects** (h) STOT-single exposure; Category 1 **Results / Target organs** Optic nerve, Central nervous system (CNS). No data available (i) STOT-repeated exposure; **Target Organs** No information available. (j) aspiration hazard; No data available **Other Adverse Effects** The toxicological properties have not been fully investigated. Symptoms / effects.both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or delayed emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation.

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	

#### 12.2. Persistence and degradability Readily biodegradable

Persistence Miscible with water, Persistence is unlikely, based on information available.

Component	Degradability
Methyl alcohol	DT50 ~ 17.2d
67-56-1 ( 60 )	>94% after 20d

#### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)	
Methyl alcohol	-0.74	<10 dimensionless	
Benzenemethanaminium, N,N,N-trimethyl-,	-3	No data available	
hvdroxide			

<u>12.4. Mobility in soil</u>	The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils
<u>12.5. Results of PBT and vPvB</u> assessment	No data available for assessment.
<u>12.6. Endocrine disrupting</u> properties Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors
<u>12.7. Other adverse effects</u> Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or suspected substance This product does not contain any known or suspected substance

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused Waste is classified as hazardous. Dispose of in accordance with the European Directives

Benzyltrimethylammonium hydroxide, 40% w/w in methanol

Products	on waste and hazardous waste. Dispose of in accordance with local regulations.				
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.				
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.				
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.				

# **SECTION 14: TRANSPORT INFORMATION**

## IMDG/IMO

<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> Technical Shipping Name <u>14.3. Transport hazard class(es)</u> Subsidiary Hazard Class <u>14.4. Packing group</u>	UN3286 Flammable liquid, toxic, corrosive, n.o.s. (BENZYLTRIMETHYLAMMONIUM HYDROXIDE) 3 6.1, 8 II
ADR	
<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> Technical Shipping Name <u>14.3. Transport hazard class(es)</u> Subsidiary Hazard Class <u>14.4. Packing group</u>	UN3286 Flammable liquid, toxic, corrosive, n.o.s. (BENZYLTRIMETHYLAMMONIUM HYDROXIDE) 3 6.1, 8 II
IATA	
<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> Technical Shipping Name <u>14.3. Transport hazard class(es)</u> Subsidiary Hazard Class <u>14.4. Packing group</u>	UN3286 FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S.* (BENZYLTRIMETHYLAMMONIUM HYDROXIDE) 3 6.1, 8 II
14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

# **SECTION 15: REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Benzyltrimethylammonium hydroxide, 40% w/w in methanol

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	Х	Х	KE-23193	Х	Х
Benzenemethanaminium, N,N,N-trimethyl-, hydroxide	100-85-6	202-895-5	-	-	Х	Х	KE-34414	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	Х	ACTIVE	X	-	Х	Х	Х
Benzenemethanaminium, N.N.N-trimethyl-, hydroxide	100-85-6	x	ACTIVE	Х	-	Х	Х	х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Benzenemethanaminium, N,N,N-trimethyl-, hydroxide	100-85-6	-	-	_

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

#### Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Benzenemethanaminium,	100-85-6	Not applicable	Not applicable
N,N,N-trimethyl-, hydroxide			

# Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl alcohol	WGK 2	Class I : 20 mg/m <sup>3</sup> (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol	Prohibited and Restricted	Group I	
67-56-1 ( 60 )	Substances		
Benzenemethanaminium, N,N,N-trimethyl-,	Prohibited and Restricted		
hydroxide	Substances		
100-85-6 ( 40 )			

#### 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

- H314 Causes severe skin burns and eye damage
- H318 Causes serious eye damage
- H370 Causes damage to organs

### Legend

CAS - Chemical Abstracts Service	<b>TSCA</b> - United States Toxic Substances Control Act Section 8(b) Inventory
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances	<b>y</b>
<ul> <li>WEL - Workplace Exposure Limit</li> <li>ACGIH - American Conference of Governmental Industrial Hygienists</li> <li>DNEL - Derived No Effect Level</li> <li>RPE - Respiratory Protective Equipment</li> <li>LC50 - Lethal Concentration 50%</li> <li>NOEC - No Observed Effect Concentration</li> <li>PBT - Persistent, Bioaccumulative, Toxic</li> </ul>	<ul> <li>TWA - Time Weighted Average</li> <li>IARC - International Agency for Research on Cancer</li> <li>Predicted No Effect Concentration (PNEC)</li> <li>LD50 - Lethal Dose 50%</li> <li>EC50 - Effective Concentration 50%</li> <li>POW - Partition coefficient Octanol:Water</li> <li>vPvB - very Persistent, very Bioaccumulative</li> </ul>

#### Benzyltrimethylammonium hydroxide, 40% w/w in methanol

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road         IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code         OECD - Organisation for Economic Co-operation and Development         BCF - Bioconcentration factor	ICAO/IATA - International Civil Aviation Organization/International Air Transport Association MARPOL - International Convention for the Prevention of Pollution from Ships ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)
Key literature references and sources for data https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:Physical hazardsOn basis of test dataHealth HazardsCalculation methodEnvironmental hazardsCalculation method

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers. Chemical incident response training.

Prepared By	Health, Safety and Environmental Department
Creation Date	22-Sep-2009
Revision Date	30-Nov-2024
Revision Summary	Not applicable.

# This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of Safety Data Sheet**